



DIMENSION DETAIL	
A	
B	
C	
D	
E	
F	
G	

SPRAY NOZZLE SPECIFICATION :

TYPE : BOTTOM SPRAY LANCE
 DOWEL PIN SIZE :
 ORIFICE SIZE :

**NOTE:- CYLINDER AIR PR. REQUIRED MINIMUM 2-3 BAR
 WITH AUTO SHUT OFF & ANTI DRIP FEATURE**

ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED								
IF IN DOUBT PLEASE ASK			MACHINING TOL. UNLESS SPECIFIED					
▽▽▽	GROUND FINISH	ANGULAR DIMS.		LINEAR DIMS.				
▽▽	SMOOTH FINISH	OVER	UPTO	TOL.	OVER	UPTO	TOL.	
▽	ROUGH FINISH	1	6	±6'	-	6	±0.1	
⊕	SCALE: N.T.S.	6	30	±10'	6	30	±0.2	
		30	120	±20'	30	120	±0.3	
		120	360	±30'	120	315	±0.5	
				M.O.C.:	SS316L	315	1000	±0.8
		DRN.	SANTOSH	DATE	05/02/18			
		CHK.	RUSHI	SIGN				
REV	DATE	DESCRIPTION	APPD.	B.A.K.	SIGN			

Spraytech®
 Systems (India) Pvt. Ltd.

CUSTOMER :

TITLE:	BOTTOM SPRAY LANCE (WS 300S)	PAGE:	1 OF 1
DWG. NO. :		REV.:	0

This document is property of M/s. SPRAYTECH SYSTEMS (INDIA) PVT. LTD. Passing on and copying of this document, Utilization and communication of its contents are prohibited unless expressly authorized. Offenders will be liable for damages.